

pumpa®

blue line

PUMPA BLUE LINE
PSP8-7/0.18L, PSP9-7.5/0.25L

submersible sewage pump

BLUE LINE PSP8-7

BLUE LINE PSP9-7.5

Single-phase submersible sewage pump. The design of the impeller protects the pump against clogging and thus enables efficient pumping of liquids with solid particles up to 15 mm and long fibers.



Technical specification

Model	blue line PSP8-7/0.18l	blue line PSP9-7.5/0.25l
Code	ZB00001158	ZB00001159
Maximum flow [m ³ /hod]	7,9	9
Maximum discharge head [m]	7	7,5
Voltage / frequency [V/Hz]	230 / 50	230 / 50
Power [W]	180	250
Connection	5/4"	5/4"
Maximum immersion depth [m]	5	5
Float switch	yes	yes
Minimum water level for operation [cm]	7	7
Maximum diameter of coarse dirt [mm]	15	15
Maximum fluid temperature [°C]	35	35
Maximum ambient temperature [°C]	40	40
Cable length [m]	6	6
Degree of protection	IP X8	IP X8
Insulation class	B	B
Weight [kg]	9	9,5
Dimension L x H x W [mm]	360 x 180 x 185	360 x 180 x 185

Application

- For draining clean or slightly contaminated water
- For irrigation
- For draining pools
- Pumping water over from tanks

Hydraulic power curve

