

pumpa®

blue line

PUMPA BLUE LINE PSP12-8.5/0.45L, PSP18-12/0.75L

submersible sewage pump

BLUE LINE PSP12-8,5

BLUE LINE PSP18-12

Single-phase submersible sewage pump. The bottom suction allows almost complete drainage, stainless steel and special cast iron protect the pump from corrosion.



Technical specification

Model	blue line PSP12-8,5/0.45l	blue line PSP18-12/0.75l
Code	ZB00001160	ZB00001161
Maximum flow [m³/hod]	12	18
Maximum discharge head [m]	8,5	12
Voltage / frequency [V/Hz]	230 / 50	230 / 50
Power [W]	450	750
Connection	2"	2"
Maximum immersion depth [m]	5	5
Float switch	yes	yes
Minimum water level for operation [cm]	7	7
Maximum diameter of coarse dirt [mm]	25	25
Maximum fluid temperature [°C]	35	35
Maximum ambient temperature [°C]	40	40
Cable length [m]	6	6
Degree of protection	IP X8	IP X8
Insulation class	B	B
Weight [kg]	18	22
Dimension L x H x W [mm]	495 x 195 x 255	535 x 195 x 255

Application

- For draining clean or contaminated water
- For irrigation
- For draining pools
- Pumping water over from tanks

Hydraulic power curve

