

High-pressure In-line Pump

Movitec

50 Hz

Type Series Booklet



Legal information/Copyright

Type Series Booklet Movitec

All rights reserved. The contents provided herein must neither be distributed, copied, reproduced, edited or processed for any other purpose, nor otherwise transmitted, published or made available to a third party without the manufacturer's express written consent.

Subject to technical modification without prior notice.

Contents

High-pressure Pumps.....	5
High-pressure In-line Pumps.....	5
Movitec	5
Main applications.....	5
Fluids handled	5
Operating data.....	5
Design details	5
Designation	7
Materials.....	10
Coating and preservation	10
Product benefits.....	10
Product information	10
Product information as per Regulation No. 1907/2006 (REACH)	10
Product information as per Regulation No. 547/2012 (for water pumps with a maximum shaft power of 150 kW) implementing "Ecodesign" Directive 2009/125/EC	11
Certifications	11
Acceptance tests and warranty	11
Selection information	12
Impeller for lower NPSH values.....	12
Information about the characteristic curve.....	13
Fluid handled.....	13
Minimum flow rate and maximum flow rate.....	13
Overview of product features / selection tables	15
Overview of fluids handled	15
Shaft seal	18
Pressure limits and temperature limits	19
Movitec A, B	19
Technical data	20
Motors.....	20
Types of connection	21
Selection charts	22
Movitec, n = 2900 rpm	22
Movitec, n = 1450 rpm	23
Characteristic curves.....	24
n = 2900 rpm	25
Movitec, 2B, n = 2900 rpm.....	25
Movitec, 2LB, n = 2900 rpm.....	26
Movitec, 4B, n = 2900 rpm.....	27
Movitec, 4LB, n = 2900 rpm	28
Movitec, 6B, n = 2900 rpm	29
Movitec, 6LB, n = 2900 rpm	30
Movitec, 10B, n = 2900 rpm	31
Movitec, 10LB, n = 2900 rpm	32
Movitec, 15B, n = 2900 rpm	33
Movitec, 15LB, n = 2900 rpm	34
Movitec, 25B, n = 2900 rpm	35
Movitec, 40B, n = 2900 rpm	36
Movitec, 60B, n = 2900 rpm	37
Movitec, 90B, n = 2900 rpm	38
Movitec, 125B, n = 2900 rpm	39
Movitec, LHS 6, n = 2900 rpm	40
n = 1450 rpm	41
Movitec, 10B, n = 1450 rpm	41
Movitec, 10LB, n = 1450 rpm	42
Movitec, 15B, n = 1450 rpm	43
Movitec, 15LB, n = 1450 rpm	44
Movitec, 25B, n = 1450 rpm	45
Movitec, 40B, n = 1450 rpm	46
Movitec, 60B, n = 1450 rpm	47
Movitec, 90B, n = 1450 rpm	48
Dimensions	49
Movitec, 2(L)B, n = 2900 rpm	49

Movitec, 4(L)B, n = 2900 rpm.....	50
Movitec, 6(L)B, n = 2900 rpm.....	51
Movitec, 10(L)B, n = 1450 rpm.....	52
Movitec, 10(L)B, n = 2900 rpm.....	53
Movitec, 15(L)B, n = 1450 rpm.....	54
Movitec, 15(L)B, n = 2900 rpm.....	55
Movitec, 25B, n = 1450 rpm.....	56
Movitec, 25B, n = 2900 rpm.....	57
Movitec, 40B, n = 1450 rpm.....	58
Movitec, 40B, n = 2900 rpm.....	59
Movitec, 60B, n = 1450 rpm.....	60
Movitec, 60B, n = 2900 rpm.....	61
Movitec, 90B, n = 1450 rpm.....	62
Movitec, 90B, n = 2900 rpm.....	63
Movitec, 125B, n = 2900 rpm.....	64
Movitec, LHS 6, n = 2900 rpm.....	65
Installation information.....	66
Terminal box positions.....	68
Scope of supply	68
Accessories.....	68
General assembly drawing with list of components.....	69
Movitec 2(L)B, 4(L)B, 6(L)B	69
Movitec 10(L)B, 15(L)B	70
Movitec 25B, 40B, 60B.....	71
Movitec 90B	72
Movitec 125B	73
Movitec LHS 6	74

High-pressure Pumps**High-pressure In-line Pumps****Movitec**

i The product illustrated as an example may include options incurring a surcharge.

Main applications

- Spray irrigation systems
- General irrigation systems
- Washing plants
- Fire-fighting systems
- Pressure boosting
- Industrial plants
- Water supply systems
- Heating, ventilation and air-conditioning systems
- Marine applications

Fluids handled

- High-temperature hot water
- Clear water
- Condensate
- Cooling water
- Fire-fighting water
- Oil
- Cleaning agents
- And others (⇒ Page 15)

Operating data**Operating properties**

Characteristic	Value	
	Movitec A	Movitec B
Flow rate	Q [m^3/h]	≤ 8,6
	Q [l/s]	≤ 2,4
Head	H [m]	≤ 401
	T [$^{\circ}\text{C}$]	≥ -15 ≤ +120
Fluid temperature		≥ -20 ≤ +140 ¹⁾
Operating pressure	p [bar]	≤ 40 ²⁾
		≤ 40 ²⁾

Design details**Design**

- High-pressure in-line pump
- Maximum pressure class PN 40
- Centrifugal pump
- Single-stage or multistage

Installation

Standard:

- Vertical installation

Optional:

- Horizontal installation

Drive

- Surface-cooled KSB squirrel-cage motor
- 3~230/400 V up to 2.2 kW
- 3~400/690 V from 3.0 kW
- Thermal class F to IEC 34-1
- Efficiency class IE3 to IEC 60034-30 (for three-phase motors ≥ 0.75 kW)
- Enclosure IP55
- Frequency 50 Hz

For VM version and motor designs V18 and V1 ≥ 3 kW:

- PTC thermistors

Shaft seal

- Uncooled maintenance-free mechanical seal
- To EN 12756
- Fixed mechanical seal
 - Mechanical seal in standard design
 - Unbalanced bellows-type seal
 - ≤ 25 bar
 - Fitted as standard for Movitec V 2B, 4B, 6B

1) For fluid temperatures > 120 °C the pressure class must not exceed PN 25.
2) The sum of inlet pressure and shut-off head must not exceed the value indicated.

- Easy Access mechanical seal
 - Easy to replace
 - Unbalanced bellows-type seal
 - ≤ 25 bar
 - Drive lantern need not be removed to replace the seal.
 - Motor rating 5.5 kW and above: Motor need not be removed.
 - Fitted as standard for Movitec 10B, 15B, 25B, 40B, 60B, 90B and Movitec VS 2B, 4B, 6B
- Cartridge seal
 - Unbalanced bellows-type design (PN 25) or special balanced design (PN 40)
 - Drive lantern need not be removed to replace the seal.
 - Motor rating 5.5 kW and above: Motor need not be removed.
 - Optionally available for all sizes except Movitec LHS 6
 - Fitted as standard for Movitec 125B

Bearings

- Tungsten carbide plain bearings at the hydraulic rotor

Designation

Designation example

Position																															
M	o	v	i	t	e	c	V	-	F	0	0	6	/	0	6	1	B	3	D	1	3	E	S	1	1	2	B	7	D	A	X
See name plate and data sheet																See data sheet															

Designation key

Position	Code	Description
1-7	Type series	
	Movitec	
8-9	Design	
	LH	Stainless steel
	V	Stainless steel
	VC	Stainless steel / grey cast iron
	VM	Stainless steel
	VS	Stainless steel
10	Connection type	
	³⁾	Oval flange
	E ⁴⁾	External thread
	F	Round flange
	I	Internal thread
	T	Tri-Clamp fitting
	V	Victaulic coupling
11-13	Size	
	002	2

	125	125
15-16	Number of stages	
	01	1

	30	30
17	Number of stages with special impeller	
	-	No stage with a special impeller
	1	One stage with a special impeller
	2	Two stages with a special impeller
	L	One stage with a special impeller for lower NPSH values
18	Product generation	
	A	Movitec up to 2009
	B	Movitec from 2010
19	Connection standard	
	0	Victaulic coupling
	1	Round flange
	2	Round flange
	3	Round flange
	4	Oval flange
	5	Oval flange
	6	Tri-Clamp fitting
	7	External thread
	8	Oval flange
	9	Round flange
20	Material variant	
	D	1.4308 - EN-GJS-400-15 - EN-GJL-250
	E	1.4308 - EN-GJS-400-15 - 1.4308
	F	1.4308 - 1.4308 - EN-GJL-250
	G	1.4308 - 1.4308 - EN-GJS-400-15

3) Blank

4) Pumps with external thread are supplied with an integrated swing check valve as standard.

Position	Code	Description
20	H	1.4308 - 1.4308 - 1.4308
	K	1.4308 - 1.4408 - EN-GJS-400-15
	L	1.4308 - 1.4408 - EN-GJL-250
	M	1.4308 - 1.4408 - 1.4308
	N	1.4308 - EN-GJS-400-15 - EN-GJL-250
	O	1.4408 - EN-GJS-400-15 - 1.4308
	P	1.4408 - 1.4308 - EN-GJL-250
	Q	1.4408 - 1.4308 - 1.4308
	R	1.4408 - 1.4408 - EN-GJL-250
	S	1.4408 - 1.4408 - EN-GJS-400-15
	T	1.4408 - 1.4408 - 1.4308
	U	EN-GJL-250 -EN-GJL-250 -EN-GJL-250
	V	EN-GJS-400-15 - EN-GJS-400-15 - EN-GJS-400-15
	W	EN-GJS-400-15 - 1.4308 - EN-GJS-400-15
	X	1.4308 - EN-GJS-400-15 - EN-GJS-400-15
	Y	1.4408 - EN-GJS-400-15 - EN-GJS-400-15
	Z	1.4408 - 1.4308 - EN-GJS-400-15
21-22	Seal code	
	11	BQ1EGG
	12	BQ1VGG
	13	Q1BEGG
	14	Q1BVGG
	15	U3U3X4GG
	16	U3U3VGG
	17	U3BVGG ⁵⁾
	18	U3BEGG
	19	U3BEGG ⁵⁾
	20	Q1AEGG
	21	Q1AVGG
	22	Q1AX4GG
	23	Q1BEGG
	24	Q1Q1VGG
	28	Q1Q1X4GG
	29	Q1Q1EGG
	35	eCarb-B eSic-Q7EGG
	36	eCarb-B eSic-Q7VGG
	39	eCarb-B eSic-Q7EGG
23	Mechanical seal design	
	F	Fixed mechanical seal
	E	Easy Access mechanical seal
	C	Cartridge mechanical seal
24	Drive	
	0	Without motor
	2	With PumpDrive 2
	A	ATEX IEC
	E	With PumpDrive 2 Eco
	N	Standard NEMA
	P	With PumpDrive
	S	Standard IEC
25-27	Motor size	
	056	NEMA 56C
	071	IEC 071
	080	IEC 080
	090	IEC 090
	100	IEC 100
	112	IEC 112
	132	IEC 132

5) For Movitec LHS 6 only

Position	Code	Description
25-27	143	NEMA 143TC
	145	NEMA 145TC
	160	IEC 160
	180	IEC 180
	182	NEMA 182TC
	184	NEMA 184TC
	200	IEC 200
	215	NEMA 215TC
	225	IEC 225
	256	NEMA 256TC
	284	NEMA 284TC
	286	NEMA 286TC
	324	NEMA 324TC
	326	NEMA 326TC
	364	NEMA 364TC
28	Pressure class	
	A	PN16 / PN25
	B	PN25
	C	PN25 / PN40
	D	PN40
29	Number of motor poles	
	5	2-pole, 50 Hz
	6	2-pole, 60 Hz
	7	4-pole, 50 Hz
	8	4-pole, 60 Hz
30	Motor specification	
	F	EXM IEC - TBH
	G	EXM NEMA
	K	EXM IEC - Movitec
	M	230 V, single-phase AC motor
	O	0.37/0.55 kW - without IE classification
	U	230 / 400 V - IE3
	V	400 / 690 V - IE3
	W	230 / 400 V - IE4/IE5 (KSB SuPremE)
31	PumpMeter	
	A	With PumpMeter
	W	Without PumpMeter
32	Design	
	- ³⁾	Standard
	X	Non-standard (BT3D, BT3)

Materials

Overview of available materials

Part No.	Description	Design			
		V	VC	VS	LHS 6
10-6	Pump shroud	1.4301		1.4404	
101	Pump casing	1.4308	EN-GJL-250 ⁶⁾ / EN-GJS-400-15 ⁷⁾	1.4408	
108	Stage casing	1.4301 ⁸⁾ / 1.4308 ⁹⁾		1.4404 ⁸⁾ / 1.4408 ⁹⁾	
160	Discharge cover	1.4301 ⁸⁾ / 1.4308 ⁹⁾		1.4404 ⁸⁾ / 1.4408 ⁹⁾	
210	Shaft	1.4057		1.4460 / 1.4401 ¹⁰⁾	
230	Impeller ¹¹⁾	1.4301 ⁸⁾ / 1.4308 ⁹⁾		1.4404 ⁸⁾ / 1.4408 ⁹⁾	
341	Drive lantern	EN-GJL-250 ¹²⁾ / EN-GJS-400-15 ¹³⁾			
412	O-ring	EPDM-WRc / ACS / ACS	EPDM	FPM / HNBR	
525	Spacer sleeve	1.4301		1.4401	
529	Bearing sleeve	Tungsten carbide / aluminium oxide			
890	Baseplate	EN-GJS-400-15 / EN-GJL-250 / 1.4308 ¹⁴⁾	-	EN-GJS-400-15 / EN-GJL-250 / 1.4308 ¹⁴⁾	
905	Tie bolt	1.4057			
920	Nut	1.4301		1.4404	
932	Circlip	1.4571			

Key to materials of pump components

Material designation / material number	ASTM
EN-GJL-250	A48 Class 35 B
EN-GJS-400-15	A5369 Grade 60-40-18
1.4057	SS 431
1.4301	SS 304
1.4308	Grade CF8M
1.4401	SS 316
1.4404	SS 316L
1.4408	Grade CF8M
1.4460	SS 329
1.4571	SS 316Ti

Coating and preservation

Coating of pump components

Component	Coating
Stainless steel components	No additional coating
Movitec VC:	
Pump casing made of grey cast iron	Cataphoretic coating
Movitec V/VS:	
Slide flanges made of grey cast iron	Cataphoretic coating
Drive lantern made of grey cast iron	Powder coating

Product benefits

- Reliable: product-lubricated plain bearings made of tungsten carbide, cast pump foot, torsion-resistant pump shroud and confined O-rings
- Long service life: corrosion-resistant hydraulic components made of stainless steel
- Easy to service: can be fitted with any standardised mechanical seal (to EN 12756)
- Flexible: various materials and connection options, extended temperature range and pressure range

Product information

Product information as per Regulation No. 1907/2006 (REACH)

For information as per chemicals Regulation (EC) No. 1907/2006 (REACH), see <http://www.ksb.com/reach>.

- 6) Movitec 2B, 4B, 6B, 10B, 15B, 25B, 40B, 60B, 125B
- 7) Movitec 90B
- 8) Movitec 2B, 4B, 6B, 10B, 15B, 25B, 40B, 60B
- 9) Movitec 90B, 125B
- 10) Movitec VS 2B, 4B up to 14 stages, 6B up to 12 stages, 10B, 15B up to 10 stages
- 11) The impellers of Movitec 125 are made of sheet metal and cast material.
- 12) Movitec 2B, 4B, 6B, 10B, 15B, 25B (≤ 4 kW) and Movitec 90B
- 13) Movitec 2B, 4B, 6B, 10B, 15B, 25B (≥ 5.5 kW) and Movitec 40B, 60B, 125B
- 14) Optional for: Movitec 2B, 4B, 6B, 10B, 15B

**Product information as per Regulation No. 547/2012
 (for water pumps with a maximum shaft power of
 150 kW) implementing "Ecodesign" Directive 2009/125/
 EC**

- Minimum efficiency index: see data sheet
- The benchmark for the most efficient water pumps is MEI ≥ 0.70 .
- Year of construction: see data sheet
- Manufacturer's name or trade mark, commercial registration number and place of manufacture: see data sheet or order documentation
- Product's type and size identifier: see data sheet
- Hydraulic pump efficiency (%) with trimmed impeller: see data sheet
- Pump performance curves, including efficiency characteristics: see documented characteristic curve
- The efficiency of a pump with a trimmed impeller is usually lower than that of a pump with full impeller diameter. Trimming of the impeller will adapt the pump to a fixed duty point, leading to reduced energy consumption. The minimum efficiency index (MEI) is based on the full impeller diameter.
- Operation of this water pump with variable duty points may be more efficient and economic when controlled, for example, by the use of a variable speed drive that matches the pump duty to the system.
- Information relevant for disassembly, recycling or disposal at end of life: see installation/operating manual
- Information on benchmark efficiency or benchmark efficiency graph for MEI = 0.70 (0.40) for the pump based on the model shown in the Figure are available at: <http://www.europump.org/efficiencycharts>

▪ **Warranties**

Warranties are given within the scope of the valid terms and conditions of sale and delivery.

Certifications

Overview

Label	Effective in:	Comment
	France	Approved in accordance with the French drinking water regulation
	United Kingdom	Approved by all water suppliers in the UK (WRAS = Water Regulations Advisory Scheme)

Acceptance tests and warranty

- Pressure test
 - to EN 809
- Leak test
 - with water
- Materials testing
 - Certificate of compliance with the order (corresponds to EN 10204)
 In the certificate of compliance with the order the manufacturer confirms by way of an informal report without specifying test results that the delivery complies with the stipulations of the purchase order.
 - Test report 2.2 on request
- Final inspection
 - Inspection certificate 3.1 to EN 10204 on request
- Hydraulic test

The duty point of each pump is guaranteed to ISO 9906:2012 Grade 3B.
 This test is always carried out using the original motor.
 The NPSH and the suction lift are not measured (3.2 certificate available).

Selection information

Impeller for lower NPSH values

An impeller for lower NPSH values is available for sizes 2, 4, 6, 10 and 15.

This type of impeller ensures that the pump's NPSH curve is significantly improved.

The solution is based on a newly developed impeller for lower NPSH values and a modified stage casing. Cavitation inside the pump can hence be prevented in the case of critical inlet conditions.

Risks of cavitation:

- Reduced lifetime of the pump due to damaged parts and unbalanced hydraulic system
- Excessive wear of pump parts or motor bearings
- Insufficient cooling and/or lubrication of the mechanical seal and pump bearing

Benefits of using impellers for lower NPSH values:

- More suitable in critical inlet conditions
- Easy adaptation to non-optimised application parameters
- The suction lift (H_p) is less crucial (the frame height of the degassing tank used in boiler feeding can be reduced).

Consequences of using impellers for lower NPSH values:

- No need to change pump installation heights or pump nozzles
- Minor adjustments to the characteristic curve

Calculation:




Fig. 1: Calculating the $NPSH_A$

$NPSH_A$	NPSH system value at operating point
$NPSH_R$	NPSH pump value at operating point (see characteristic curve of the pump)
H_b	Atmospheric pressure [mWc]
H_o	Positive pressure (with tank closed)
H_p	Suction lift [mWc]
H_v	Vapourisation pressure [mWc] (see vapourisation pressure diagram for water)
H_f	Friction losses in pipes and accessories [mWc]
H_z	Safety margin (min. 0,5 m)
x	Minimum pressure

Result:

If the minimum pressure (x) is positive, there is no risk of cavitation.

If the minimum pressure (x) is negative, there is a risk of cavitation which can be avoided by using an impeller for lower NPSH values.

Another option is to change one of the other values so that the value becomes positive.

Example:

- Boiler feed water: 105 °C
- Positive height of tank: 2 m
- Positive pressure in tank: 3 mWc
- Flow rate: 5 m³/h
- Head: 100 m (10 bar)
- Size selected: 4

Calculation of positive pressure on suction flange:

Calculation of positive pressure on suction flange:	Standard impeller	Special impeller for lower NPSH values
Atmospheric pressure [mWc]	10,3	10,3
Positive pressure (with tank closed)	3,0	3,0
Suction lift	2,0	2,0
Vaporisation pressure [mWc] (see water vaporisation pressure diagram)	-12,5	-12,5
Friction losses in pipes and accessories [mWc]	-1,0	-1,0
Safety margin (min. 0,5 m)	-0,5	-0,5
NPSH pump value at operating point (see characteristic curve of the pump)	-2,1	-0,8
Minimum pressure	-0,8	+0,5
Conclusion	Cavitation will occur.	No cavitation




Fig. 2: Vaporisation pressure diagram (H_v) for water

Information about the characteristic curve

NPSH [m], [ft]:

- The NPSH values given in the individual characteristic curves are minimum values which correspond to the cavitation limit.
- A safety margin of at least 0.5 m must be added when selecting the pump to compensate for measuring inaccuracies.
- The NPSH curves reflect average values.
- A safety margin of 0.5 m must be added to the NPSH value of the characteristic curve when selecting a system.

P [kW], [hp]:

- The power input is indicated per stage ($St = 1$) and/or per stage with a smaller impeller ($St = -1$). The pump input power can be calculated accordingly. Calculation: value indicated in the diagram ($St = 1$) \times number of stages + value indicated in the diagram ($St = -1$) \times number of stages with a smaller impeller Example 1, Movitec 90/4: $P = (St = 1) \times 4$
Example 2, Movitec 90/4-1: $P = (St = 1) \times 3 + (St = -1)$
Example 3, Movitec 90/4-2: $P = (St = 1) \times 2 + (St = -1) \times 2$

Fluid handled

The actual operating conditions must always be checked (concentration, temperature, solids content). Penetration of air into the system must be avoided by all means.

If the fluid handled contains solids such as steel chips or steel chip dust, check the permissible particle concentration with KSB.

Minimum flow rate and maximum flow rate

Minimum flow rate and maximum flow rate Q at a fluid temperature $\leq +20^\circ\text{C}$

Movitec	Q			
	2 poles		4 poles	
	Min. [m³/h]	Max. [m³/h]	Min. [m³/h]	Max. [m³/h]
2B	0,2	3,3	-	-
4B	0,4	6,5	-	-
6B	0,6	9,0	-	-
10B	1,1 ¹⁵⁾	13,2	0,5	6,6
15B	1,6 ¹⁵⁾	22,5	0,8	11,3
25B	2,8	35,0	1,4	17,5
40B	4,0	54,0	2,0	27,0

15) For pumps with VdS certification the minimum flow rate Qmin is 5 % of the permissible flow rate.

Movitec	Q			
	2 poles		4 poles	
	Min.	Max.	Min.	Max.
	[m³/h]	[m³/h]	[m³/h]	[m³/h]
60B	6,0	76,0	3,0	38,0
90B	8,5	110,0	4,3	53,9
125B	12,2	160,0	-	-
LHS 6	0,8	8,6	-	-




Fig. 3: Minimum flow rate required as a function of fluid temperature at a fluid temperature > +20 °C

Overview of product features / selection tables

Overview of fluids handled

The data refer to the chemical resistance of the materials. The relevant regulations / standards governing individual pump applications have to be complied with.

If the operating conditions differ from the data given (e.g. mixed products) or if the fluids handled are not included in the table below, please contact the manufacturer.

- Temperature ranges:
 - Reference temperature: +20 °C
 - For temperatures <0 °C: contact the manufacturer.
 - For temperatures > +50 °C: check and observe the vapour pressure of the fluid handled.
 - Max. temperature = +120 °C, unless indicated otherwise.
- Max. concentration = 100 % unless indicated otherwise.
- Mechanical seal silicon carbide / carbon (Q1B): not suitable for fluids containing solid substances. This rule also covers particles developing as a result of salt crystallisation at low fluid temperatures.
- Mechanical seal tungsten carbide / tungsten carbide (U3U3): solids content max. 20 ppm (depending on particle size), with the exception of corrosive fluids. Fluids with a higher solids content are not permitted (ppm = 1 mg/kg).
- Caution: High temperatures will increase corrosion (reference temperature = +20 °C).
- Under unfavourable conditions (high temperatures, deposits, long idle periods), chloride contents of more than 300 mg/l may result in localised corrosion.

Selection of pump design and mechanical seal design depending on the fluid to be handled

Fluid handled			Variant / Size																	
Substance contained	Max. percent-age	T _{max.}	V				VC					VS					LHS			
	[%]	[°C]	13	14	15	16	18	13	14	15	16	18	23	13	14	15	16	18	17	19
Alum, acid-free	≤ 3	+50	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-
Alum, acid-free	≤ 3	+80	-	-	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-
Alkaline solution, bottle rinsing, max. 2 % sodium hydroxide	≤ 100	+40	-	-	X	-	-	-	-	X	-	-	-	-	-	X	-	-	-	-
Alcohol																				
▪ Butanol	≤ 100	+60	X	-	-	-	-	X	-	-	-	-	-	X	X	-	-	-	-	-
▪ Ethanol	≤ 100	+60	X	-	-	-	-	X	-	-	-	-	-	X	X	-	-	-	-	-
▪ Propanol	≤ 100	+80	X	-	-	-	-	X	-	-	-	-	-	X	X	-	-	-	-	-
▪ Spirits (40 % ethanol)	≤ 100	+60	X	-	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-
Wine (white, red)	≤ 100	+60	X	X	-	-	-	-	-	-	-	-	-	-	X	X	-	-	X	X
Tartaric acid	≤ 100	+60	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X
Ammonium bicarbonate	≤ 10	+40	X	-	-	-	-	X	-	-	-	-	-	X	X	-	-	-	-	-
Aluminium sulphate, acid-free	≤ 5	+50	-	-	-	X	-	-	-	-	-	-	-	-	-	-	-	X	-	-
Aluminium sulphate, acid-free	≤ 5	+60	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X	-
Ammonium sulphate	≤ 20	+60	X	-	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-
Calcium acetate, acid-free	≤ 10	+60	X	-	-	-	-	X	-	-	-	-	-	X	X	-	-	-	-	-
Calcium nitrate, acid-free	≤ 10	+60	-	-	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-
Ferric sulphate (II)	≤ 5	+80	-	-	-	X	-	-	-	-	-	-	-	-	-	-	-	X	-	-
Water-oil emulsion (95 %, 5 %), free of solids	≤ 100	+80	-	X	-	-	-	-	X	-	-	-	-	-	X	-	-	-	-	-
Ethylene glycol base antifreeze, inhibited, closed system	≤ 20	+110	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	X ¹⁶⁾	X	-	X	-	-	-
	≤ 25	+110	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	X ¹⁶⁾	X	-	X	-	-	-
	≤ 30	+110	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	X ¹⁶⁾	X	-	X	-	-	-
	≤ 35	+110	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	X ¹⁶⁾	X	-	X	-	-	-
	≤ 40	+110	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	X ¹⁶⁾	X	-	X	-	-	-
	≤ 45	+110	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	X ¹⁶⁾	X	-	X	-	-	-
	≤ 50	+110	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	X ¹⁶⁾	X	-	X	-	-	-
Ethylene glycol base antifreeze, inhibited, open system	≤ 20	+110	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	-	-	-	-	-	X ¹⁶⁾	X	-	X	-	-	-
	≤ 25	+110	X ¹⁶⁾	X	-	X	-	X ¹⁶⁾	-	-	-	-	-	X ¹⁶⁾	X	-	X	-	-	-

16) ≤ 100 °C

Fluid handled			Variant / Size																	
Substance contained	Max. percent-age	T _{max.}	V				VC				VS				LHS					
	[%]	[°C]	13	14	15	16	18	13	14	15	16	18	23	13	14	15	16	18	17	19
Ethylene glycol base antifreeze, inhibited, open system	≤ 30	+110	X ¹⁶⁾	X	-	X	-	-	-	-	-	-	-	X ¹⁶⁾	X	-	X	-	-	-
	≤ 35	+110	X ¹⁶⁾	X	-	X	-	-	-	-	-	-	-	X ¹⁶⁾	X	-	X	-	-	-
	≤ 40	+110	X ¹⁶⁾	X	-	X	-	-	-	-	-	-	-	X ¹⁶⁾	X	-	X	-	-	-
	≤ 45	+110	X ¹⁶⁾	X	-	X	-	-	-	-	-	-	-	X ¹⁶⁾	X	-	X	-	-	-
	≤ 50	+110	X ¹⁶⁾	X	-	X	-	-	-	-	-	-	-	X ¹⁶⁾	X	-	X	-	-	-
Glycerine	≤ 40	+80	X	X	-	-	-	X	X	-	-	-	-	X	X	X	-	-	-	-
Glycols (pure)	≤ 100	+100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Diethylene glycol	≤ 100	+100	X	X	-	-	-	X	X	-	-	-	-	X	X	X	-	-	-	-
Ethylene glycol	≤ 100	+100	X	X	-	-	-	X	X	-	-	-	-	X	X	X	-	-	-	-
Potassium hydroxide	≤ 5	+40	-	-	X	-	-	-	X	-	-	-	-	-	-	-	X	-	-	-
Potassium nitrate, acid-free	≤ 5	+30	-	-	X	-	-	-	-	X	-	-	-	-	-	-	X	-	-	-
Potassium sulphate, acid-free	≤ 3	+20	-	X	-	-	-	-	X	-	-	-	-	-	-	-	X	-	-	-
Copper sulphate	≤ 5	+80	-	-	X	-	-	-	-	-	-	-	-	-	-	-	X	-	-	-
Magnesium sulphate	≤ 10	+80	-	X	-	-	-	-	-	-	-	-	-	-	-	-	X	-	-	X
Milk	≤ 100	+60	X	X	-	-	-	-	-	-	-	-	-	X	X	-	-	-	-	-
Lactic acid	≤ 40	+60	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X
Miscella ¹⁷⁾	≤ 100	+40	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Sodium carbonate	≤ 6	+60	X	-	-	-	-	X	-	-	-	-	-	X	X	-	-	-	-	X
Sodium hydroxide	≤ 5	+60	-	-	X	-	-	-	-	X	-	-	-	-	-	-	X	-	-	-
Sodium nitrate, acid-free	≤ 10	+30	X	-	-	-	-	X	-	-	-	-	-	X	X	-	-	-	-	X
Sodium nitrate, acid-free	≤ 10	+60	X	-	-	-	-	X	-	-	-	-	-	-	-	-	-	-	-	X
Sodium sulphate, acid-free	≤ 5	+60	X	-	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	X
Oil																				
▪ Peanut oil	≤ 100	+90	-	X	-	-	-	-	X	-	-	-	-	-	X	-	-	-	-	-
▪ Peanut oil	≤ 100	+100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X
▪ Hydraulic oil ¹⁷⁾	≤ 100	+80	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X
▪ Linseed oil, ≤ 3 % H ₂ SO ₄	≤ 100	+20	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-
▪ Linseed oil, ≤ 3 % H ₂ SO ₄	≤ 100	+60	-	-	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-
▪ Linseed oil	≤ 100	+60	-	X	-	-	-	-	X	-	-	-	-	-	-	X	-	-	-	X
▪ Corn oil	≤ 100	+100	-	X	-	-	-	-	X	-	-	-	-	-	X	-	-	-	-	X
▪ Mineral oil ¹⁷⁾	≤ 100	+80	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X
▪ Vegetable oil ¹⁷⁾	≤ 100	+100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X
▪ Rapeseed oil	≤ 100	+100	-	X	-	-	-	-	X	-	-	-	-	-	X	-	-	-	-	X
▪ Salad oil	≤ 100	+100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X
▪ Lubricating oil ¹⁷⁾	≤ 100	+100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X
▪ Silicone oil ¹⁷⁾	≤ 100	+60	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X
▪ Soybean oil	≤ 100	+100	-	X	-	-	-	-	X	-	-	-	-	-	X	-	-	-	-	X
▪ Turbine oil (no SDF oils) ¹⁷⁾	≤ 100	+100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X
▪ Oil-water mixtures	≤ 100	+100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X
Paraffin ¹⁷⁾	≤ 100	+100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X
Kerosene	≤ 100	+80	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	X
Polyethylene glycol ¹⁷⁾	≤ 100	+80	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X X
Polyglycol ¹⁷⁾	≤ 100	+80	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X -
Crude oil ¹⁷⁾	≤ 100	+80	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X -
Crude oil condensate ¹⁷⁾	≤ 100	+80	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X -
Juice (fruit and sugar juice)	≤ 100	+60	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	X -
Acid																				

17) Fluid details are required in this case.

Fluid handled			Variant / Size																		
Substance contained	Max. percent-age	T _{max.}	V				VC					VS				LHS					
	[%]	[°C]	13	14	15	16	18	13	14	15	16	18	23	13	14	15	16	18	17	19	
▪ Acetic acid	≤ 10	+60	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-	-	
▪ Acetic acid	≤ 5	+60	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-	-	
▪ Tannic acid	≤ 20	+80	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-	
▪ Maleic acid	≤ 10	+60	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-	
▪ Lactic acid	≤ 5	+60	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-	
▪ Lactic acid	≤ 40	+60	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-	
▪ Phosphoric acid	≤ 5	+20	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-	
▪ Sulphuric acid	≤ 5	+20	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X	-	-	
▪ Tartaric acid	≤ 8	+40	-	-	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-	
▪ Citric acid	≤ 25	+30	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-	
▪ Citric acid	≤ 10	+30	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-	
Fuel																					
▪ Diesel oil	≤ 100	+80	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-	
▪ Fuel oil	≤ 100	+80	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-	
▪ Jet fuel	≤ 100	+80	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-	
Trisodium phosphate	≤ 4	+80	-	-	X	-	-	-	X	-	-	-	-	-	-	X	-	-	-	-	
Water																					
▪ Deionised water (fully desalinated)	≤ 100	+140	X	-	-	-	X ¹⁸⁾	-	-	-	-	-	-	-	X	-	-	-	X ¹⁸⁾	-	X
▪ Distilled water	≤ 100	+140	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X ¹⁹⁾
▪ Dealkalised water	≤ 100	+120	-	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-
▪ Decarbonised water	≤ 100	+120	-	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-
▪ Swimming pool water (no brine)	≤ 100	+100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X
▪ Permeate (osmosis)	≤ 100	+140	X	-	-	-	X ¹⁸⁾	-	-	-	-	-	-	-	X	-	-	-	X ¹⁸⁾	-	-
▪ Partly desalinated water	≤ 100	+120	-	-	X	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-
▪ Fire-fighting water	≤ 100	+60	-	-	X	-	X	-	X	-	-	X	-	-	X	-	X	-	X	-	-
▪ Heating water in accordance with VDI 2035	≤ 100	+100	X	-	-	-	X	X	-	-	-	X	X	X	-	-	-	X	-	X ¹⁹⁾	
▪ Hot water treated in accordance with VdTÜV 1466	≤ 100	+140	X ¹⁶⁾	-	-	-	X ¹⁸⁾	X ¹⁶⁾	-	-	-	X ¹⁸⁾	X ¹⁶⁾	X ¹⁶⁾	-	-	-	X ¹⁸⁾	-	X ¹⁹⁾	
▪ Boiler feed water to VdTÜV 1466	≤ 100	+140	X ¹⁶⁾	-	-	-	X ¹⁸⁾	X ¹⁶⁾	-	-	-	X ¹⁸⁾	X ¹⁶⁾	X ¹⁶⁾	-	-	-	X ¹⁸⁾	-	X ¹⁹⁾	
▪ Condensate treated in acc. with VdTÜV 1466	≤ 100	+140	X ¹⁶⁾	-	-	-	X ¹⁸⁾	X ¹⁶⁾	-	-	-	X ¹⁸⁾	X ¹⁶⁾	X ¹⁶⁾	-	-	-	X ¹⁸⁾	-	X ¹⁹⁾	
▪ Vapour condensate (brewery)	≤ 100	+140	X ¹⁶⁾	-	-	-	X ¹⁸⁾	X ¹⁶⁾	-	-	-	X ¹⁸⁾	X ¹⁶⁾	X ¹⁶⁾	-	-	-	X ¹⁸⁾	-	-	
▪ Cooling water	≤ 100	+100	-	-	-	X	-	-	-	-	-	X	-	-	-	-	-	X	-	-	
▪ Tap water	≤ 100	+60	X	-	-	-	-	X	-	-	-	-	-	-	X	-	-	-	-	-	
▪ Brewing water	≤ 100	+60	X	-	-	-	-	X	-	-	-	-	-	-	X	-	-	-	-	-	
▪ Ice water (brewery)	≤ 100	+60	X	-	-	-	-	X	-	-	-	-	-	-	X	-	-	-	-	-	
▪ Drinking water / tap water	≤ 100	+60	X	-	-	-	-	X	-	-	-	-	-	-	X	-	-	-	-	X	
▪ Hot water (brewery)	≤ 100	+60	X	-	-	-	-	X	-	-	-	-	-	-	X	-	-	-	-	-	

18) ≤ 120 °C, depending on the pressure classes

19) ≤ 120 °C

Fluid handled			Variant / Size																	
Substance contained	Max. percent-age	T _{max.}	V				VC					VS				LHS				
			[%]	[°C]	13	14	15	16	18	13	14	15	16	18	23	13	14	15	16	18
▪ Clean water	≤ 100	+60	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	-	-
▪ Brackish water	≤ 100	+15	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X	-	-	-
▪ Seawater	≤ 100	+15	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X	-	-	-
▪ Raw water	≤ 100	+60	-	-	X	-	-	-	-	X	-	-	-	-	-	X	-	-	-	-
▪ Grey water, slightly contaminated water	≤ 100	+60	-	-	X	-	-	-	-	X	-	-	-	-	-	X	-	-	-	-
▪ River water	≤ 100	+60	-	-	X	-	-	-	-	X	-	-	-	-	-	X	-	-	-	-
▪ Lake water	≤ 100	+60	-	-	X	-	-	-	-	X	-	-	-	-	-	X	-	-	-	-
▪ Dam water	≤ 100	+60	-	-	X	-	-	-	-	X	-	-	-	-	-	X	-	-	-	-
▪ Surface water	≤ 100	+60	-	-	X	-	-	-	-	X	-	-	-	-	-	X	-	-	-	-
▪ Fresh water	≤ 100	+60	-	X	-	-	-	-	-	X	-	-	-	-	-	X	-	-	-	-
▪ Barrier water	≤ 100	+70	-	-	-	X	-	-	-	-	X	-	-	-	-	-	X	-	-	-
▪ Rinsing water	≤ 100	+70	-	-	-	X	-	-	-	-	X	-	-	-	-	-	X	-	-	-
▪ Rainwater, with strainer	≥ 20	+60	-	-	-	X	-	-	-	-	X	-	-	-	-	-	X	-	-	-
▪ Water-glycol mixture	≤ 100	+100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X

Shaft seal

Available mechanical seals

Mechanical seal							T		Pres- sure [bar]	Certification
Seal code	Type	Material			Design		Min.	Max.		
		Mechanical seal	Shaft seal ring	F	E	C	[°C]	[°C]		
11	M12G-G60	BQ1EGG	Ca/SiC/EPDM	X	X	X	-20	+100	10	-
12	M12G-G60	BQ1VGG	Ca/SiC/FPM	X	X	X	-20	+120	10	-
13	RMG12-G606	Q1BEGG	SiC/Ca/EPDM	X	X	X	-20	+100	25	WRAS
14	RMG12-G606	Q1BVGG	SiC/Ca/FPM	X	X	X	-20	+120	25	-
15	RMG12-G606	U3U3X4GG	TuC/TuC/HNBR	X	X	X	-20	+120 ²⁰⁾	25	-
16	RMG12-G606	U3U3VGG	TuC/TuC/FPM	X	X	X	-20	+120 ²⁰⁾	25	-
17	M37GN2/16-00-R	U3BVGG	TuC/Ca/FPM ²¹⁾	X	-	-	-20	+120 ²²⁾	40	-
18	RMG12-G606	U3BEGG	TuC/Ca/EPDM	X	X	X	-20	+120 ²⁰⁾	25	-
19	M37GN2/16-00-R	U3BEGG	TuC/Ca/EPDM ²¹⁾	X	-	-	-20	+120 ²²⁾	40	-
20	H7N	Q1AEGG	SiC/Ca/EPDM	-	-	X	-20	+120 ²³⁾	40	-
21	H7N	Q1AVGG	SiC/Ca/FPM	-	-	X	-20	+120 ²³⁾	40	-
22	H7N	Q1AX4GG	SiC/Ca/HNBR	-	-	X	-20	+120 ²³⁾	40	-
23	RMG12-G606	Q1BEGG	SiC/Ca/EPDM	X	X	X	-20	+100	25	-
24	MG12-G60	Q1Q1VGG	SiC1/SiC1/FPM	X	X	X	-20	+120	10	-
28	MG12-G60	Q1Q1X4GG	SiC1/SiC1/HNBR	X	X	X	-20	+120	10	-
29	MG12-G60	Q1Q1EGG	SiC1/SiC1/EPDM	X	X	X	-20	+100	10	-
35	RMG12-G6	eCarb-B eSic-Q7EGG	eCa/eSic/EPDM	-	-	X	-20	+120	25	WRAS
36	MG12-G6	eCarb-B eSic-Q7VGG	eCa/eSic/FPM	-	-	X	-20	+120	25	-
37	RMG12-G606	U3AVGG	TuC/Ca/FPM	-	-	X	-20	+120 ²⁰⁾	25	-

Key to mechanical seal materials

Description	Code to EN 12756	Seal face materials / secondary seals
Primary ring	B	Hard carbon, resin-impregnated

20) Temperatures up to +140 °C if the pressure does not exceed 16 bar

21) For Movitec LHS6 only

22) If the pressure does not exceed 25 bar. Temperatures up to +80 °C if the pressure does not exceed 40 bar

23) Temperatures up to +140 °C if the pressure does not exceed 25 bar

Description	Code to EN 12756	Seal face materials / secondary seals
Primary ring	U3	Tungsten carbide (CrNiMo binder)
	Q1	Silicon carbide, sintered without pressure
	eCarb-B	Carbon graphite, resin-impregnated
Mating ring	A	Carbon graphite, antimony-impregnated
	B	Hard carbon, resin-impregnated
	U3	Tungsten carbide (CrNiMo binder)
	Q1	Silicon carbide, sintered without pressure
	eSic-Q7	Silicon carbide
Elastomer	E	EPDM (ethylene propylene rubber)
	V	FPM (fluoroelastomer)
	X4	HNBR
Spring	G	CrNiMo steel
Other metal parts	G	CrNiMo steel

Pressure limits and temperature limits

Movitec A, B

Movitec A

Pressure limits and temperature limits

Movitec	p	T
	[bar]	[°C]
LHS6	40	120

Movitec B

The pump's pressure limits and temperature limits are indicated on the name plate.

Technical data
Motors

- Efficiency class IE3 to IEC 60034-30 (for three-phase motors $\geq 0.75 \text{ kW}$)

Technical data of the motors

P_N	U_N	I_A	I_A/I_N	cos φ	Tolerance U_N	n	η	L_p	Cable gland	Maximum frequency of starts
[kW]	[V]	[A]			[%]	rpm	[%]	[dB]		[/h]
Movitec 2B, 4B, 6B, 25B, 40B, 60B, 90B, 125B										
0,37	1 × 230	2,6	3,7	0,92	+/-10	2750	67,00	58	1x M18×1,5	20
0,55	1 × 230	3,69	3,9	0,92	+/-10	2760	70,00	56	1x M18×1,5	20
0,75	1 × 230	5	3,9	0,92	+/-10	2780	70,00	56	1x M20×1,5	20
1,1	1 × 230	6,68	4,3	0,95	+/-10	2790	75,00	58	1x M20×1,5	20
1,5	1 × 230	8,99	4,8	0,95	+/-10	2800	76,00	58	1x M20×1,5	20
2,2	1 × 230	13,04	4,8	0,95	+/-10	2800	77,00	58	1x M20×1,5	20
0,37	230/400	1,64/0,94	4,6	0,78	+/-10	2750	74,20	58	1x M20×1,5	20
0,55	230/400	2,31/1,33	5,2	0,75	+/-10	2790	77,60	58	1x M20×1,5	20
0,75	230/400	2,92/1,68	6,8	0,8	+/-10	2855	80,50	60	2x M20×1,5	25
1,1	230/400	4,17/2,4	7	0,8	+/-10	2855	82,70	60	2x M25×1,5	25
1,5	230/400	5,08/2,92	7,7	0,88	+/-10	2900	84,20	63	2x M25×1,5	25
2,2	230/400	7,22/4,15	7,7	0,89	+/-10	2900	86,00	63	2x M25×1,5	25
3	230/400	9,71/5,59	8,8	0,89	+/-10	2910	87,10	63	2x M25×1,5	20
3	400/690	5,59/3,24	8,8	0,89	+/-10	2910	87,10	63	2x M25×1,5	20
4	230/400	13,0/7,45	8,5	0,88	+/-10	2910	88,10	63	2x M25×1,5	20
4	400/690	7,45/4,32	8,5	0,88	+/-10	2910	88,10	63	2x M25×1,5	20
5,5	230/400	17,4/10,0	8,8	0,89	+/-10	2925	89,20	68	2x M32×1,5	20
5,5	400/690	10,0/5,80	8,8	0,89	+/-10	2925	89,20	68	2x M32×1,5	20
7,5	230/400	23,2/13,4	8,8	0,9	+/-10	2925	89,80	68	2x M32×1,5	20
7,5	400/690	13,4/7,74	8,8	0,9	+/-10	2925	89,80	68	2x M32×1,5	20
11	230/400	33,6/19,3	8	0,9	+/-10	2940	91,20	68	2x M32×1,5	15
11	400/690	19,3/11,2	8	0,9	+/-10	2940	91,20	68	2x M32×1,5	15
15	230/400	45,5/26,2	8	0,9	+/-10	2940	91,90	68	2x M32×1,5	15
15	400/690	26,2/15,2	8	0,9	+/-10	2940	91,90	68	2x M32×1,5	15
18,5	230/400	55,2/31,8	8	0,91	+/-10	2945	92,40	68	2x M32×1,5	15
18,5	400/690	31,8/18,4	8	0,91	+/-10	2945	92,40	68	2x M32×1,5	15
22	230/400	65,5/37,6	8,5	0,91	+/-10	2955	92,70	70	2x M32×1,5	15
22	400/690	37,6/21,8	8,5	0,91	+/-10	2955	92,70	70	2x M32×1,5	15
30	230/400	89,7/51,6	8,5	0,9	+/-10	2965	93,30	73	2x M32×1,5	15
30	400/690	51,6/29,9	8,5	0,9	+/-10	2965	93,30	73	2x M50×1,5	15
37	230/400	110/63,3	8,5	0,9	+/-10	2965	93,70	73	2x M50×1,5	15
37	400/690	63,3/36,7	8,5	0,9	+/-10	2965	93,70	73	2x M50×1,5	15
45	230/400	134/76,8	8,5	0,9	+/-10	2970	94,00	75	2x M50×1,5	15
45	400/690	76,8/44,5	8,5	0,9	+/-10	2970	94,00	75	2x M50×1,5	15
0,55	230/400	2,34/1,34	5,3	0,73	+/-10	1425	80,70	57	1x M20×1,5	20
0,75	230/400	3,13/1,8	6,5	0,73	+/-10	1425	82,50	57	1x M20×1,5	20
1,1	230/400	4,21/2,42	6,5	0,78	+/-10	1440	84,40	58	1x M20×1,5	20
1,5	230/400	5,59/3,21	7	0,79	+/-10	1440	85,30	58	1x M25×1,5	20
2,2	230/400	7,86/4,52	7,5	0,81	+/-10	1445	86,70	59	2x M25×1,5	20
3	230/400	10,6/6,10	7,5	0,81	+/-10	1445	87,70	59	2x M25×1,5	20
3	400/690	6,10/3,53	7,5	0,81	+/-10	1445	87,70	59	2x M25×1,5	20
4	230/400	14,0/8,05	8,5	0,81	+/-10	1450	88,50	60	2x M25×1,5	20
4	400/690	8,05/4,66	8,5	0,81	+/-10	1450	88,60	60	2x M25×1,5	20
5,5	230/400	19,0/10,9	8,5	0,81	+/-10	1460	89,90	60	2x M32×1,5	20
5,5	400/690	10,9/6,34	8,5	0,81	+/-10	1460	89,60	60	2x M32×1,5	20
7,5	230/400	25,4/14,6	8,5	0,82	+/-10	1460	90,40	60	2x M32×1,5	20
7,5	400/690	14,6/8,47	8,5	0,82	+/-10	1460	90,40	60	2x M32×1,5	20
Movitec 10B, 15B										
0,75	1 × 230	5	3,9	0,92	+/-10	2780	70,00	56	1x M20×1,5	20
1,1	1 × 230	6,68	4,3	0,95	+/-10	2790	75,00	58	1x M20×1,5	20

P _N [kW]	U _N [V]	I _A [A]	I _A /I _N	cos φ	Tolerance U _N [%]	n rpm	η [%]	L _p [dB]	Cable gland	Maximum frequency of starts
										[l/h]
1,5	230/400	5,3/3,0	7,3	0,85	+/-10	2925	84,2	55	1x M20x1,5	50
2,2	230/400	7,5/4,3	8,0	0,86	+/-10	2910	85,9	55	1x M20x1,5	30
3	230/400	10,2/5,8	9,3	0,85	+/-10	2920	87,1	57	2x M20x1,5	30
3	400/690	5,8/3,3	9,3	0,85	+/-10	2920	87,1	57	2x M20x1,5	30
4	230/400	12,8/7,4	8,4	0,89	+/-10	2930	88,1	58	2x M20x1,5	30
4	400/690	7,4/4,3	8,4	0,89	+/-10	2930	88,1	58	2x M20x1,5	30
5,5	230/400	17,3/10	8,8	0,89	+/-10	2940	89,2	63	2x M25x1,5	20
5,5	400/690	10/5,8	8,8	0,89	+/-10	2940	89,2	63	2x M25x1,5	20
7,5	230/400	23/13,3	9,2	0,89	+/-10	2940	90,1	63	2x M25x1,6	20
7,5	400/690	13,3/7,7	9,2	0,89	+/-10	2940	90,1	63	2x M25x1,5	20
11	230/400	33,4/19,3	7,3	0,9	+/-10	2945	91,2	69	2x M32x1,5	15
11	400/690	19,3/11,2	7,3	0,9	+/-10	2945	91,2	69	2x M32x1,5	15
15	230/400	45,4/26,2	7,4	0,9	+/-10	2945	91,9	69	2x M32x1,5	15
15	400/690	26,2/15,2	7,4	0,9	+/-10	2945	91,9	69	2x M32x1,5	15

Types of connection

Overview of available connection types

Description	Design							
	V / VS	VF	VSF ²⁴⁾	VCF	LHS	VE / VME ²⁴⁾	VV / VMV / VSV	VT / VST / VMT ²⁴⁾
Connection type	Oval flange / Internal thread	Round flange				External thread	Vicatulic coupling	Tri-Clamp fitting
Standard	ISO 228-1	EN 1092-1/EN 1092-2 ASME B 16.1 JIS				EN1092-2	ISO 228-1	-
Material	1.4308 ²⁵⁾ / 1.4408 ²⁶⁾	EN-GJS-400-15	1.4308	EN-GJL-250 ²⁷⁾ / EN-GJS-400-15 ²⁸⁾	1.4408	EN-GJS-400-15	1.4408	1.4408
Maximum pressure class	PN 16	PN 40				PN 40	PN 16	PN 40

24) The stainless steel baseplate shown is available as an option.

25) For Movitec V


26) For Movitec VS

27) Movitec 2B, 4B, 6B, 10B, 15B, 25B, 40B, 60B, 125B


28) Movitec 90B

Selection charts

Movitec, n = 2900 rpm



Movitec, n = 1450 rpm



Characteristic curves

The characteristic curves are based on the following principles:


- Tolerances to ISO 9906:2012 Grade 3B

The characteristic curves were measured under the following conditions:


- Motor used:
 - Standardised KSB motor with integrated frequency inverter
- Fluid properties:
 - Deaerated water
 - Fluid temperature: +20 °C
 - Density: 1.0 kg/dm³
 - Kinematic viscosity: 1 mm²/s

$n = 2900 \text{ rpm}$


Movitec, 2B, $n = 2900 \text{ rpm}$




St = 1 | P per stage

Movitec, 2LB, n = 2900 rpm


St = 1 | P per stage


Movitec, 4B, n = 2900 rpm


St = 1 | P per stage


Movitec, 4LB, n = 2900 rpm


St = 1 | P per stage


Movitec, 6B, n = 2900 rpm




St = 1 | P per stage

Movitec, 6LB, n = 2900 rpm



St = 1 | P per stage

Movitec, 10B, n = 2900 rpm



St = 1 | P per stage

Movitec, 10LB, n = 2900 rpm



St = 1 | P per stage

Movitec, 15B, n = 2900 rpm



St = 1 | P per stage


Movitec, 15LB, n = 2900 rpm


St = 1 | P per stage

Movitec, 25B, n = 2900 rpm



St = 1 | P per stage

Movitec, 40B, n = 2900 rpm


Movitec, 60B, n = 2900 rpm



St = 1 | P per stage

St = -1 | P per stage with a smaller impeller

Movitec, 90B, n = 2900 rpm



St = 1 | P per stage

St = -1 | P per stage with a smaller impeller

Movitec, 125B, n = 2900 rpm


St = 1 | P per stage

St = -1 | P per stage with a smaller impeller


Movitec, LHS 6, n = 2900 rpm



St = 1 | P per stage

 *) $Q_{min} \leq 40^{\circ}\text{C}$


n = 1450 rpm

Movitec, 10B, n = 1450 rpm




Movitec, 10LB, n = 1450 rpm



St = 1 | P per stage


Movitec, 15B, n = 1450 rpm


St = 1 | P per stage


Movitec, 15LB, n = 1450 rpm


St = 1 | P per stage


Movitec, 25B, n = 1450 rpm

 St = 1 P per stage


Movitec, 40B, n = 1450 rpm


St = 1 | P per stage







Movitec, 60B, n = 1450 rpm


St = 1 | P per stage

Movitec, 90B, n = 1450 rpm



Dimensions
Movitec, 2(L)B, n = 2900 rpm


Dimensions of Movitec V(S), VE, V(S)V, V(S)T, V(C/S)F








Fig. 4: Connections of Movitec V, VS

Fig. 5: Connections of Movitec VV, VSV

Fig. 6: Connections of Movitec VT, VST

Fig. 7: Connections of Movitec VF, VSF

Fig. 8: Connections of Movitec VCF

Fig. 9: Connections of Movitec V(M)E
Dimensions

Number of stages	E1 [mm]	E2 [mm]	Design					
			V(S) ^{29), VE^{29), V(S)V, V(S)T}}		V(C/S)F		V(M)E	
			F1 [mm]	F2 [mm]	F1 [mm]	F2 [mm]	F1 [mm]	
2	138	109	480	259	505	284	420	
3	138	109	501	280	526	305	441	
4	138	109	523	302	548	327	463	
5	138	109	544	323	569	348	484	
6	138	109	566	345	591	370	506	
7	138	109	587	366	612	391	-	
8	138	109	609	388	634	413	-	
9	160	150	651	419	376	444	-	
10	160	150	673	441	698	466	-	
11	160	150	719	462	744	487	-	
12	160	150	741	484	766	509	-	
14	160	150	784	527	809	552	-	
16	185	160	854	580	879	605	-	
18	185	160	897	623	922	648	-	
20	185	160	940	666	965	691	-	
22	185	160	1007	709	1032	734	-	
24	185	160	1050	752	1075	777	-	
26	185	160	1093	795	1118	820	-	
28	185	160	1136	838	1161	863	-	
30	185	160	1179	881	1204	906	-	

29) Available with a maximum of 20 stages


Movitec, 4(L)B, n = 2900 rpm


Dimensions of Movitec V(S), VE, V(S)V, V(S)T, V(C/S)F



Fig. 10: Connections of Movitec V, VS

Fig. 11: Connections of Movitec VV, VSV

Fig. 12: Connections of Movitec VT, VST

Fig. 13: Connections of Movitec VF, VSF

Fig. 14: Connections of Movitec VCF

Fig. 15: Connections of Movitec V(M)E
Dimensions

Number of stages	E1 [mm]	E2 [mm]	Design				
			V(S) ⁽³⁰⁾ , VE ⁽³⁰⁾ , V(S)V, V(S)T		V(C/S)F		V(M)E
			F1 [mm]	F2 [mm]	F1 [mm]	F2 [mm]	F1 [mm]
2	138	109	480	259	505	284	420
3	138	109	501	280	526	305	441
4	138	109	523	302	548	327	463
5	160	150	565	333	590	358	528
6	160	150	612	355	637	380	556
7	160	150	633	376	658	401	-
8	185	160	682	408	707	433	-
9	185	160	703	429	728	454	-
10	185	160	725	451	750	476	-
11	185	160	770	472	795	497	-
12	185	160	792	494	817	519	-
14	185	160	835	537	860	562	-
16	185	160	908	590	933	615	-
18	205	175	951	633	976	658	-
20	205	175	994	676	1019	701	-
22	220	190	1031	719	1059	744	-
24	220	190	1077	762	1102	787	-
26	220	190	1120	805	1145	830	-







30) Available with a maximum of 16 stages

Movitec, 6(L)B, n = 2900 rpm








Dimensions of Movitec V(S), VE, V(S)V, V(S)T, V(C/S)F









Dimensions of Movitec V(M)E


Fig. 16: Connections of Movitec V, VS

Fig. 17: Connections of Movitec VV, VSV

Fig. 18: Connections of Movitec VT, VST

Fig. 19: Connections of Movitec VF, VSF

Fig. 20: Connections of Movitec VCF

Fig. 21: Connections of Movitec V(M)E
Dimensions

Number of stages	E1 [mm]	E2 [mm]	Design				
			V(S) ³¹ , VE ³¹ , V(S)V, V(S)T		V(C/S)F		V(M)E
			F1 [mm]	F2 [mm]	F1 [mm]	F2 [mm]	F1 [mm]
2	138	109	487	266	512	291	426
3	160	150	533	301	558	326	496
4	160	150	583	326	608	351	521
5	160	150	608	351	633	376	546
6	185	160	660	386	685	411	-
7	185	160	685	411	710	436	-
8	185	160	734	436	759	461	-
9	185	160	759	461	784	486	-
10	185	160	784	486	809	511	-
11	205	175	839	521	864	546	-
12	205	175	864	546	889	571	-
14	205	175	914	596	939	621	-
16	220	190	961	646	986	671	-
18	220	190	1011	696	1036	721	-
20	260	220	1224	822	1249	847	-
22	260	220	1274	872	1299	897	-
24	260	220	1324	922	1349	947	-
26	260	220	1374	972	1399	997	-

Movitec, 10(L)B, n = 1450 rpm

 Dimensions of Movitec V(S),
 V(S)V, V(S)T, V(C/S)F

Fig. 22: Connections of Movitec V, VS

Fig. 23: Connections of Movitec VV, VSV

Fig. 24: Connections of Movitec VT, VST

Fig. 25: Connections of Movitec VF, VSF

Fig. 26: Connections of Movitec VCF
Dimensions







Number of stages	E1 [mm]	E2 [mm]	Design			
			V(S), V(S)V, V(S)T		V(C/S)F	
			F1 [mm]	F2 [mm]	F1 [mm]	F2 [mm]
1	157	112	603	346	603	346
2	157	112	603	346	603	346
3	157	112	629	372	629	372
4	157	112	656	399	656	399
5	157	112	682	425	682	425
6	157	112	709	452	709	452
7	157	112	735	478	735	478
8	157	112	762	505	762	505
9	157	112	788	531	788	531
10	157	112	815	558	815	558
11	157	112	841	584	841	584
13	157	133	967	672	967	672
15	180	145	975	700	975	700
17	180	145	1028	753	1028	753
19	180	145	1081	806	1081	806
21	180	145	1134	859	1134	859

Movitec, 10(L)B, n = 2900 rpm

 Dimensions of Movitec V(S),
 V(S)V, V(S)T, V(C/S)F

Fig. 27: Connections of Movitec V, VS

Fig. 28: Connections of Movitec VV, VSV

Fig. 29: Connections of Movitec VT, VST

Fig. 30: Connections of Movitec VF, VSF

Fig. 31: Connections of Movitec VCF
Dimensions







Number of stages	E1 [mm]	E2 [mm]	P ³²⁾ [mm]	Design			
				V(S) ³³⁾ , V(S)V, V(S)T		V(C/S)F	
				F1 [mm]	F2 [mm]	F1 [mm]	F2 [mm]
1	157	133	-	578	346	578	578
2	157	133	-	578	346	526	578
3	157	133	-	629	372	548	629
4	200	148	-	690	409	569	690
5	200	148	-	716	435	591	716
6	200	148	-	743	462	612	743
7	215	157	-	815	498	634	815
8	215	157	-	842	525	676	842
9	248	168	-	907	551	698	907
10	248	168	-	934	578	744	934
11	248	168	-	960	604	766	960
13	288	197	300	1169	737	809	1169
15	288	197	300	1222	790	879	1222
17	288	197	300	1275	843	922	1275
19	288	197	300	1328	896	965	1328
21	288	197	300	1381	949	1032	1381

32) For motors > 5.5 kW only

33) Available with a maximum of 13 stages

Movitec, 15(L)B, n = 1450 rpm

 Dimensions of Movitec V(S),
 V(S)V, V(S)T, V(C/S)F

Fig. 32: Connections of Movitec V, VS

Fig. 33: Connections of Movitec VV, VSV

Fig. 34: Connections of Movitec VT, VST

Fig. 35: Connections of Movitec VF, VSF

Fig. 36: Connections of Movitec VCF
Dimensions


Number of stages	E1 [mm]	E2 [mm]	Design			
			V(S), V(S)V, V(S)T		V(C/S)F	
			F1 [mm]	F2 [mm]	F1 [mm]	F2 [mm]
1	157	112	603	346	613	356
2	157	112	603	346	613	356
3	157	112	629	372	639	382
4	157	112	656	399	666	409
5	157	112	682	425	692	435
6	157	133	747	452	752	462
7	180	145	763	488	773	498
8	180	145	790	515	800	525
9	180	145	816	541	826	551
10	180	145	868	568	878	578
11	180	145	894	594	904	604
13	180	145	947	647	957	657
15	200	155	1028	710	1038	720
17	200	155	1081	763	1091	773

Movitec, 15(L)B, n = 2900 rpm

 Dimensions of Movitec V(S),
 V(S)V, V(S)T, V(C/S)F

Fig. 37: Connections of Movitec V, VS

Fig. 38: Connections of Movitec VV, VSV

Fig. 39: Connections of Movitec VT, VST

Fig. 40: Connections of Movitec VF, VSF

Fig. 41: Connections of Movitec VCF
Dimensions

Number of stages	E1 [mm]	E2 [mm]	P ³⁴⁾ [mm]	Design			
				V(S) ³⁵⁾ , V(S)V, V(S)T		V(C/S)F	
				F1 [mm]	F2 [mm]	F1 [mm]	F2 [mm]
1	157	133	-	603	346	613	356
2	200	148	-	637	356	664	366
3	215	157	-	709	392	720	402
4	248	168	-	775	419	744	429
5	288	197	300	957	525	937	535
6	288	197	300	983	551	963	561
7	288	197	300	1010	578	988	588
8	288	197	300	1036	604	1014	614
9	340	223	350	1194	661	1175	671
10	340	223	350	1220	687	1201	697
11	340	223	350	1257	724	1228	724
13	340	223	350	1310	777	1281	777
15	340	223	350	1363	830	1334	830
17	340	223	350	1416	883	1387	883



34) For motors > 5.5 kW only

35) Available with a maximum of 11 stages

Movitec, 25B, n = 1450 rpm



Dimensions of Movitec V(C/S)F

Motor flange version with tapped holes


Fig. 42: Connections of Movitec VF, VSF

Fig. 43: Connections of Movitec VCF

Dimensions

Number of stages	E1 [mm]	E2 [mm]	Design	
			V(C/S)F	
			F1 [mm]	F2 [mm]
1	180	145	683	408
2	180	145	748	473
3	180	145	813	538
4	180	145	878	603
5	180	145	943	668
6	180	145	1033	733
7	180	145	1098	798
8	200	155	1186	868
9	200	155	1251	933
10	200	155	1316	998
11	200	155	1381	1063
12	200	155	1490	1128



Movitec, 25B, n = 2900 rpm


Number of stages	E1	E2	P	Design	
	V(C/S)F			F1	F2
	[mm]	[mm]	[mm]	[mm]	[mm]
7	315	260	350	1428	924
8	315	260	350	1493	989
9	315	260	350	1558	1054
10	315	265	350	1667	1119
11	315	265	350	1732	1184
12	360	275	350	1824	1249

Dimensions of Movitec V(C/S)F Dimensions of Movitec V(C/S)F

Motor flange version with tapped holes

Motor flange version with clearance holes



Fig. 44: Connections of Movitec VF, VSF

Fig. 45: Connections of Movitec VCF

Dimensions (motor flange version with tapped holes)

Number of stages	E1	E2	P	Design	
	V(C/S)F			F1	F2
	[mm]	[mm]	[mm]	[mm]	[mm]
1	180	190	-	706	408
2	223	190	190	793	478




Dimensions (motor flange version with clearance holes)

Number of stages	E1	E2	P	Design	
	V(C/S)F			F1	F2
	[mm]	[mm]	[mm]	[mm]	[mm]
3	260	260	300	1036	634
4	260	260	300	1099	699
5	315	260	350	1298	794
6	315	260	350	1363	859

Movitec, 40B, n = 1450 rpm


Dimensions of Movitec V(C/S)F Dimensions of Movitec V(C/S)F

i Motor version V18


i Motor version V1

Fig. 46: Connections of Movitec VF, VSF

Fig. 47: Connections of Movitec VF, VSF - interchangeable range

Fig. 48: Connections of Movitec VCF

Dimensions (motor flange version with tapped holes)


Number of stages	E1	E2	P	Design	
	V(C/S)F			F1	F2
	[mm]	[mm]	[mm]	[mm]	[mm]
4	200	155	-	1039	721
5	200	155	-	1161	799
6	200	155	-	1239	877
7	233	166	-	1270	955
8	233	166	-	1348	1033
9	233	166	-	1426	1111



Dimensions (motor flange version with clearance holes)

Number of stages	E1	E2	P	Design	
	V(C/S)F			F1	F2
	[mm]	[mm]	[mm]	[mm]	[mm]
10	260	190	300	1679	1279

Movitec, 40B, n = 2900 rpm


Dimensions of Movitec V(C/S)F Dimensions of Movitec V(C/S)F

i Motor version V18

Fig. 49: Connections of Movitec VF, VSF (PN 16, PN 25)


i Motor version V1

Fig. 52: Connections of Movitec VCF (DN 65)

Fig. 53: Connections of Movitec VCF (DN 80)


Dimensions (motor flange version with tapped holes)

Number of stages	E1	E2	P	Design	
	V(C/S)F			F1	F2
	[mm]	[mm]	[mm]	[mm]	[mm]
1-1	200	155	-	805	487
1	223	166	-	802	487

Dimensions (motor flange version with clearance holes)



Number of stages	E1	E2	P	Design	
	V(C/S)F			F1	F2
	[mm]	[mm]	[mm]	[mm]	[mm]
2-2	260	190	300	1057	655
2	260	190	300	1055	655
3-2	315	260	350	1267	763
3	315	260	350	1267	763
4-2	315	260	350	1345	841
4	315	260	350	1345	841
5-2	315	265	350	1467	919
5	315	265	350	1467	919
6-2	315	265	350	1545	997
6	360	275	350	1572	997
7-2	360	275	350	1650	1075
7	400	340	400	1745	1075
8-2	400	340	400	1823	1153
8	400	340	400	1823	1153
9-2	400	340	400	1901	1231
9	400	340	400	1901	1231
10-2	400	340	400	1979	1309
10	400	340	400	1979	1309

Fig. 50: Connections of Movitec VF, VSF (PN 16, PN 25 - interchangeable range)

Fig. 51: Connections of Movitec VF, VSF (PN 40)

Movitec, 60B, n = 1450 rpm


Dimensions of Movitec V(C/S)F Dimensions of Movitec V(C/S)F

i Motor version V18


i Motor version V1

Fig. 54: Connections of Movitec VF, VSF

Fig. 55: Connections of Movitec VCF

Dimensions (motor flange version with tapped holes)


Number of stages	E1 [mm]	E2 [mm]	P [mm]	Design	
				V(C/S)F F1 [mm]	F2 [mm]
3	200	155	-	961	643
4	200	155	-	1083	721
5	233	166	-	1114	799
6	233	166	-	1192	877

Dimensions (motor flange version with clearance holes)








Number of stages	E1 [mm]	E2 [mm]	P [mm]	Design	
				V(C/S)F F1 [mm]	F2 [mm]
7	260	190	300	1445	1045
8	260	190	300	1523	1123
9	260	190	300	1636	1201
10	260	190	300	1714	1279

Movitec, 60B, n = 2900 rpm


Dimensions of Movitec V(C/S)F

i Motor version V18


Dimensions of Movitec V(C/S)F



i Motor version V1

Fig. 56: Connections of Movitec VF, VSF (PN 16)

Fig. 57: Connections of Movitec VF, VSF (PN 25, PN 40)

Fig. 58: Connections of Movitec VCF (PN 16)

Fig. 59: Connections of Movitec VCF (PN 25, PN 40)

Dimensions (motor flange version with tapped holes)




Number of stages	E1	E2	P	Design	
	V(C/S)F			F1	F2
	[mm]	[mm]	[mm]	[mm]	[mm]
1-1	223	190	-	802	487


Dimensions (motor flange version with clearance holes)

Number of stages	E1	E2	P	Design	
	V(C/S)F			F1	F2
	[mm]	[mm]	[mm]	[mm]	[mm]
1	260	190	300	979	577
2-2	260	260	300	1055	655
2	315	260	350	1189	685
3-2	315	265	350	1267	763
3	315	265	350	1311	763
4-2	315	265	350	1389	841
4	360	275	350	1416	841
5-2	360	340	350	1494	919
5	400	340	400	1589	919
6-2	400	340	400	1667	997
6	400	340	400	1667	997
7-2	400	340	400	1745	1075
7	400	340	400	1745	1075
8-2	400	340	400	1823	1153
8	450	365	450	1863	1153
9-2	450	365	450	1941	1231

Movitec, 90B, n = 1450 rpm

Fig. 63: Connections of Movitec VCF (PN 25, PN 40)
Dimensions

Number of stages	E1	E2	P	Design	
	V(C/S)F			F1	F2
	[mm]	[mm]	[mm]	[mm]	[mm]
5-2	260	190	300	1477	1077
5-1	260	190	300	1477	1077
5	260	190	300	1477	1077
6-2	260	190	300	1586	1186
6-1	260	190	300	1586	1186
6	260	190	300	1586	1186

Dimensions of Movitec V(C/S)F

Fig. 60: Connections of Movitec VF, VSF(PN 16)

Fig. 61: Connections of Movitec VF, VSF (PN 25, PN 40)

Fig. 62: Connections of Movitec VCF (PN 16)

Movitec, 90B, n = 2900 rpm


Dimensions of Movitec V(C/S)F




Fig. 64: Connections of Movitec VF, VSF(PN 16)




Fig. 67: Connections of Movitec VCF (PN 25, PN 40)

Dimensions

Number of stages	E1 [mm]	E2 [mm]	Design	
			V(C/S)F	
			F1 [mm]	F2 [mm]
1-1	260	190	1043	641
1	260	190	1041	641
2-2	315	260	1284	780
2-1	315	260	1284	780
2	315	260	1284	780
3-2	315	260	1437	889
3-1	360	275	1464	889
3	360	275	1464	889
4-2	400	340	1668	998
4-1	400	340	1668	998
4	400	340	1668	998
5-2	400	340	1777	1107
5-1	400	340	1777	1107
5	400	340	1777	1107
6-2	450	365	1926	1216
6-1	450	365	1926	1216
6	450	365	1926	1216




Fig. 65: Connections of Movitec VF, VSF (PN 25, PN 40)







Fig. 66: Connections of Movitec VCF (PN 16)


Movitec, 125B, n = 2900 rpm


Dimensions of Movitec V(C/S)F



Fig. 68: Connections of Movitec VF, VSF, VCF (PN 16)

Fig. 69: Connections of Movitec VF, VSF, VCF (PN 25, PN 40)

Dimensions

Number of stages	E1	E2	Design	
			V(C/S)F	
	F1	F2		
	[mm]	[mm]	[mm]	[mm]
1	315	260	1243	740
2-2	315	260	1417	867
2-1	360	275	1444	867
2	400	340	1539	867
3-2	400	340	1669	994
3-1	400	340	1669	994
3	400	340	1669	994
4-2	450	365	1829	1121

Movitec, LHS 6, n = 2900 rpm


Dimensions of Movitec LHS6


Fig. 70: Connections of Movitec LHS6

Dimensions

Number of stages	E1	E2	F1	F2
	[mm]	[mm]	[mm]	[mm]
10	260	190	928	599
12	260	190	1015	658
14	315	260	1250	718
16	315	260	1310	808
18	315	260	1369	867
20	315	260	1429	927

Installation information

Standard:

- Vertical installation

(⇒ Page 49)

Optional:

- Horizontal installation

(for motor ratings up to and including 7.5 kW in systems where the installation conditions do not allow vertical installation)


Movitec 2(L)B, 4(L)B, 6(L)B


Fig. 71: a) Pump bracket b) Pump set

Installation dimensions of the pump bracket as a function of the motor rating

P _N	A	B	C ³⁶⁾	D		H	[kg]	Mat. No.
				-, E, T, V	F			
[kW]								
0.37/0.55 (2-pole)	100	100	F2+49	82	107	120	2	48895741
0.75/1.10 (2-pole)	100	100	F2+49	82	107	120	2,3	48895742
1.50/2.20 (2-pole)	100	100	F2+47	82	107	120	2,5	48895743
3.00/4.00 (2-pole)	100	100	F2+47	82	107	120	3	48895744
5.50/7.50 (2-pole)	100	210	F2-18	82	107	170	3,5	48895745


Movitec 10(L)B, 15(L)B


Fig. 72: a) Pump bracket b) Pump set


36) F2: see the section on Dimensions

Installation dimensions of the pump bracket as a function of the motor rating

P _N	A	B	C ³⁶⁾	D		H	[kg]	Mat. No.
				-, E, F, T, V 10B	F, T, V 15B			
[kW]				[mm]				
0.75/1.10 (2-pole)	130	130	F2+49	111,5	121,5	140	2,786	01338571
0.55/0.75 (4-pole)								
1.50/2.20 (2-pole)	130	130	F2+47	111,5	121,5	140	2,799	01338572
1.10/1.50 (4-pole)								
3.00/4.00 (2-pole)	130	130	F2+47	111,5	121,5	140	2,766	01338573
2.20/4.00 (4-pole)								
5.50/7.50 (2-/4-pole)	130	210	F2-18	111,5	121,5	170	3,116	01338574

Movitec 25B

a)



b)





Fig. 73: a) Pump bracket b) Pump set

Installation dimensions of the pump bracket as a function of the motor rating

P _N	A	B	C ³⁶⁾	D	H	[kg]	Mat. No.
[kW]				[mm]			
1.50/2.20 (2-pole)	170	180	F2+47	136,5	170	2,799	01498693
3.00/4.00 (2-pole)	170	180	F2+47	136,5	170	2,799	01498694
5.50/7.50 (2-pole)	170	210	F2-16	136,5	170	3,116	01498695

Movitec 40B, 60B

a)



b)





Fig. 74: a) Pump bracket b) Pump set

Installation dimensions of the pump bracket as a function of the motor rating



P _N	A	B	C ³⁶⁾	D	H	[kg]	Mat. No.
[kW]				[mm]			
3.00/4.00 (2-pole)	190	180	F2-16	165	180	2,799	01582128
2.20/4.00 (4-pole)							
5.50/7.50 (2-/4-pole)	190	250	F2-20	165	180	3,116	01582129

Movitec 90B

a)



b)


Fig. 75: a) Pump bracket b) Pump set


Installation dimensions of the pump bracket as a function of the motor rating

P_N [kW]	A	B	C³⁶⁾ [mm]	D	H	[kg]	Mat. No.
5.50/7.50 (2-/4-pole)	210	250	F2-16	165	180	3,8	48895593


Terminal box positions

Top view of terminal box positions


P3 = position 3
 Standard Movitec V/
 Standard Movitec VS




P6 = position 6



P9 = position 9
 Standard Movitec VME



P12 = position 12
 Not for Movitec VME


Scope of supply

Depending on the model, the following items are included in the scope of supply:

- Pump
- Electric motor

Accessories

Possible accessories:

- Frequency inverter, see type series booklet PumpDrive (4074.5)

General assembly drawing with list of components

Movitec 2(L)B, 4(L)B, 6(L)B





Fig. 76: General assembly drawing of Movitec 2(L)B, 4(L)B, 6(L)B


List of components

Part No.	Description	Part No.	Description
10-6	Pump shroud	560	Pin
101	Pump casing	681	Coupling guard
108	Stage casing	723	Flange
160	Cover	800	Motor
210	Shaft	862	Coupling
230	Impeller	890	Baseplate
341	Drive lantern	901	Hexagon head bolt
400	Gasket	903	Vent plug
412	O-ring	905	Tie bolt
433	Mechanical seal	914	Hexagon socket head cap screw
471	Seal cover	920	Nut
525	Spacer sleeve	930	Safety device
529	Bearing sleeve	932	Circlip
554	Washer	950	Spring

Movitec 10(L)B, 15(L)B

Fig. 77: General assembly drawing of Movitec 10(L)B, 15(L)B


List of components

Part No.	Description	Part No.	Description
10-6	Pump shroud	554	Washer
101	Pump casing	560	Pin
108	Stage casing	681	Coupling guard
131	Inlet ring	723	Flange
160	Cover	800	Motor
210	Shaft	862	Coupling
230	Impeller	890	Baseplate
341	Drive lantern	901	Hexagon head bolt
400	Gasket	903	Vent plug
412	O-ring	905	Tie bolt
433	Mechanical seal	914	Hexagon socket head cap screw
471	Seal cover	920	Nut
525	Spacer sleeve	930	Safety device
529	Bearing sleeve	932	Circlip
544	Threaded bush	950	Spring

Movitec 25B, 40B, 60B

Fig. 78: General assembly drawing of Movitec 25B, 40B, 60B


List of components

Part No.	Description	Part No.	Description
10-6	Pump shroud	554	Washer
101	Pump casing	560	Pin
108	Stage casing	681	Coupling guard
131	Inlet ring	800	Motor
160	Cover	862	Coupling
210	Shaft	890	Baseplate
230	Impeller	901	Hexagon head bolt
341	Drive lantern	903	Vent plug
412	O-ring	905	Tie bolt
433	Mechanical seal	914	Hexagon socket head cap screw
509	Intermediate ring	920	Nut
525	Spacer sleeve	930	Safety device
529	Bearing sleeve	932	Circlip
544	Threaded bush		

Movitec 90B

Fig. 79: General assembly drawing of Movitec 90B

List of components


Part No.	Description	Part No.	Description
108	Stage casing	580	Cap
160	Cover	681	Coupling guard
230	Impeller	722	Flange adapter
341	Drive lantern	801	Flanged motor
412	O-ring	862	Coupling
433	Mechanical seal	890	Baseplate
471	Seal cover	901	Hexagon head bolt
500	Ring	904	Grub screw
503	Impeller wear ring	914	Hexagon socket head cap screw
525	Spacer sleeve	920	Nut
529	Bearing sleeve	930	Safety device
554	Washer	932	Circlip

Movitec 125B

Fig. 80: General assembly drawing of Movitec 125B

List of components

Part No.	Description	Part No.	Description
10-6	Pump shroud	554.01	Washer
101	Pump casing	580	Cap
108.01/02	Stage casing	68-3.02	Cover plate
131	Inlet ring	681	Coupling guard
160	Cover	722	Flange adapter
210	Shaft	801	Flanged motor
230	Impeller	862	Coupling
341.02	Drive lantern	890	Baseplate
412.01/.04/.06/.07/.10	O-ring	901.07	Hexagon head bolt
433	Mechanical seal	903.01/.02	Screw plug
471	Seal cover	904	Grub screw
500	Ring	905	Tie bolt
502.02	Casing wear ring	914.01/.03/.05	Hexagon socket head cap screw

Part No.	Description	Part No.	Description
503	Impeller wear ring	920.02.03	Nut
525.01/.02/.03/.04/.05/.07	Spacer sleeve	930	Safety device
529	Bearing sleeve	932	Circlip

Movitec LHS 6

Fig. 81: General assembly drawing of Movitec LHS 6

List of components

Part No.	Description	Part No.	Description
10-6	Pump shroud	560	Pin
101	Pump casing	681	Coupling guard
108	Stage casing	722	Flange adapter
210	Shaft	801	Flanged motor
230	Impeller	862	Coupling
341	Drive lantern	901	Hexagon head bolt
411	Joint ring	903	Vent plug
412	O-ring	905	Tie bolt
433	Mechanical seal	914	Hexagon socket head cap screw
525	Spacer sleeve	920	Nut
529	Bearing sleeve	930	Safety device
554	Washer	932	Circlip



KSB SE & Co. KGaA
Johann-Klein-Straße 9 • 67227 Frankenthal (Germany)
Tel. +49 6233 86-0
www.ksb.com